digital™ MATERIAL SAFETY DATA SHEET

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: April 21, 1992

Supersedes: August 9, 1991

Product Name: Fuser Wick

Part Number(s): LN08X-AB

Use: For use with Image Transfer Device

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST IARC	CARCINOGEN LIST NTP	CARCINOGEN LIST OSHA	SARA 313
None								

Fuser Wick is classified as an article. Wick contains fuser oil. See section 8 for Safe Handling/Preventive Measures.

All ingredients contained in this product are on the US TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - Not applicable
Vapor Pressure - Not applicable
Vapor Density - Not applicable
Appearance - Plastic container with wick
Freezing Point - Not applicable
Melting/Softening Point - Not applicable
Solubility in Water - < 0.1%
Percent Volatile - None
Evaporation Rate - Not applicable
Odor and Odor Threshold- None
pH - Not applicable
Specific Gravity - Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None
Auto-Ignition Temperature - Not applicable
Hazardous Combustion Products - Carbon monoxide, carbon dioxide
Unusual Fire or Explosion Hazards - None
Special Fire Fighting Procedure - None
Flammable Limits - None
Extinguishing Media - Water, foam, dry chemical, carbon dioxide

© Digital Equipment Corporation. 1992. All rights reserved.

SECTION 5 - REACTIVITY DATA

Stability - Stable
Hazardous Decomposition Products - Not available
Conditions to Avoid - Temperature above melting
Incompatibility - None
Hazardous Polymerization -None

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- Primary route of entry is dermal. Prolonged exposure can lead to accumulation of fuser oil on skin. No evidence of toxic response is expected. Potential exposure under normal use conditions should present no hazard.
Animal Experiment- (based on testing of fuser oil)
Acute- Oral LD50- >35 g/kg (practically non-toxic);
Dermal LD50- >2 g/kg;
Inhalation LC50- N.D. Non-irritating to skin and eyes.
Chronic/Other Will not cause sensitization, cancer, mutagenicity, or teratogenicity.
Additional Information- Aquatic LC_{50} > 500mg/l.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

(Applies to fuser oil)
If Inhaled - Not applicable.
If on Skin - Promptly wash skin with soap and water.
If in Eyes - Flush eyes with large quantities of water for at least 15 minutes.
If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Personal Protective Equipment - None for normal use.
Engineer Control - Not needed.
Waste Disposal - No special Requirements.
Procedures for Leaks or Spills- Not applicable
Work Practices - None
Storage Requirement- Keep containers closed, store in cool, dry area.
Handling Procedure/Equipment- None
Labelling- None;
WHMIS Classification- Not applicable

SECTION 9 - TRANSPORTATION REQUIREMENTS

None